

PRODUCT-DETAILS

KSFS 460

KSFS 460 Phase busbar



General Information

Extended Product Type	KSFS 460
Product ID	2CGD000785P0784
EAN	7331980004874
Catalog Description	KSFS 460 Phase busbar
Long Description	Kabeldon phase busbar rated 400 A. IP 2X protection against accidental contact. Suitable for use together with busbar support KSST which is purchased separately.

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85381000
Country of Origin	Sweden (SE)

Dimensions

Product Net Width	784 mm
Product Net Height	30 mm
Product Net Depth / Length	20 mm
Product Net Weight	0.586 kg

Technical

Rated Insulation Voltage (U _i)	1000 V
Rated Operational Voltage	690 V
Rated Peak Withstand Current Low Voltage (I _{pk})	55 kA
Rated Short-time Withstand Current Low Voltage (I _{cw})	for 1 s 21 kiloampere rms
Rated Conditional Short-Circuit Current (I _{nc})	(3//250 A fuse, 690 V) 50 kiloampere rms (3//250 A fuse, 690 V) 3315AFuse690V; 85 kiloampere rms

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CGC0020
REACH Declaration	2CGC0049
RoHS Information	2CGC0038

Classifications

ETIM 7	EC001522 - Busbar
ETIM 8	EC001522 - Busbar
eClass	V11.1 : 27370303
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)
E-Number (Finland)	5451690

Categories

Low Voltage Products and Systems → Cable Distribution Cabinets → Kabeldon Cable Distribution Cabinets → Cable Distribution Cabinets Accessories

