



Surface LED fitting with plastic cover - IP44

Light fitting BRSB 6x12 LED 840, opal PMMA cover, 375mm, IP44, sensor mw

Code: BRSB4KO375V2/NDSM

EAN: 8595073796780



Vlastnosti svítidla

Product category:	Ceiling / wall luminaires	Degree of protection (IP):	IP44
Color housing:	White	With movement sensor:	Yes
Material housing:	Steel	Suitable for wall mounting:	Yes
Suitable for surface mounting:	Yes	Suitable for ceiling mounting:	Yes

Světelný zdroj

Lamp type:	LED not exchangeable	Effective luminous flux (lm):	2700
System power (W):	27	Luminaire efficacy (lm/W):	100
Color temperature (K):	4000	Color rendering index CRI:	80-89
Rated life time L80/B50 (h):	80000	With lamp:	Yes
Colour of light:	White		
Energy efficiency class of the built-in lamp:	A++, A+, A (LED)		

Optický systém

Optical system:	KO	Light outlet:	Direct
Light sharing:	Symmetric	Material cover:	Plastic, opal
Radiation angle:	Open beam/diffuse		

Rozměry

Outer diameter (mm):	375	Height/depth (mm):	108
Weight (kg):	1,5		

Elektrické vlastnosti

Protection class:	I	Connection type:	Pinching contact
Voltage type:	AC	Type of control gear:	LED operating device current-controlled
Nominal voltage (V):	220...240	Control gear included:	Yes
No dim function:	Yes		