

















Technical sheet

Industrial weatherproof luminaire

MODUS VLO 7000, wide body 1570mm, LED 840, body PC, opal PC cover, IP65, driver 1400mA

Code: VLO8000L2W4ND

This product contains a light source with energy efficiency class C



Luminaire properties

Product category:	Ceiling / wall luminaires	Effective luminous flux (lm):	7500
System power (W):	60	Luminaire efficacy (lm/W):	125
Rated lifetime L80/B50 (h):	80000	Degree of protection (IP):	IP65
Color housing:	Grey	Impact strength:	IK07
Suitable for suspended mounting:	Yes		
Material housing:	Plastic		
Light source included:	Yes	Suitable for wall mounting:	Yes
Suitable for surface mounting:	Yes	Rated ambient temperature (°C):	0+40
Suitable for ceiling mounting:	Yes	Made in Czech republic:	Yes

Light source

Light source type:	LED	Color temperature (K):	4000
Color rendering index CRI:	80-89	Replaceability:	Replaceable light source by professional, replaceable ballast
Light source type:	1990420184004	Energy efficiency class:	С

Optical system

Optical system:	СО	Light outlet:	Direct
Light sharing:	Symmetric	Material cover:	Plastic, opal
Radiation angle:	Extreme wide beam >80°		

Dimensions

Length (mm):	1570	Width (mm):	136
Height/depth (mm):	90	Built-in length (mm):	1200
Size version:	L	Weight (kg):	2,3

Electrical values

Protection class:	I	Voltage type:	AC
Type of control gear:	LED operating device current-controlled	Nominal voltage (V):	220240
Control gear included:	Yes	No dim function:	Yes
Indoor use only:	Yes		