

EXQ Easy™ 300/500 V

EXQ Easy™ 300/500 V 3G2,5

Nexans Ref.: 14110451

Country Ref.: 0445734

EAN 13: 7330000079298

The cable may be used for permanent installation on ladders, directly in walls, concrete, in conduits or ducts. For use indoors and outdoors but not in ground or water. The cable have protection against exposure of UV light.

DESCRIPTION

The cable is a halogen free, XLPE insulated and HFFR sheathed house wiring cable with circular, solid copper conductors. The cable is designed according to SS 424 02 19-5. The conductors have resistance and number of wires according to EN 60228 class 1. The cores are identified by colours according to HD 308. The sheath is marked: Cable type/ size/ NEXANS GS /year+month/metre marking. The cable meets the requirements for fire classification according to CPR Dcas2d2a2 and have protection against exposure of UV light according to HD 626 S1 part 2.5.1. The conductor insulation shall be protected against UV light that can occur for example in light fixtures and light signs. The cable is certified by Intertek SEMKO.

Lifemark(TM) recycling marking

The external surface of the outer sheath is embossed with a text which specifies all components in the polymers and prepares the cable for future recycling.

Certification

Certified by Intertek SEMKO.

Quality and environmental management system

Certified according to ISO 9001, IRIS, ISO/TS 16949 and ISO 14001.



Lifemark™

DECLARATION OF PERFORMANCE

Dca-s2,d2,a2

STANDARDS

National Factory standard;
SS 424 02 19-5



Conductor flexibility
Solid



Halogen free
Yes



Rated Voltage Uo/U
(Um)
300 / 500 V



Minimum
installation
temperature
-10 °C



Maximum operating
temperature
70 °C



Ambient static op.
temp
-40 - 70 °C



Bending factor
when laying
5 (xD)



Bending factor
installed
3 (xD)

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Nexans is indicative only and shall not be binding on Nexans or be treated as constituting a representation on the part of Nexans.

Generated 1/6/23 www.nexans.se Page 1 / 2

EXQ Easy™ 300/500 V

EXQ Easy™ 300/500 V 3G2,5

CHARACTERISTICS

Construction characteristics

Conductor material	Copper
Conductor shape	Circular
With Green/Yellow core	Yes
Conductor flexibility	Solid
Insulation	XLPE 70 degrees
Outer sheath	HFFR (polyolefin)
Colour	White
Halogen free	Yes
With smaller neutral conductor	No

Dimensional characteristics

Number of cores	3
Conductor cross-section	2.5 mm ²
Conductor diameter	1.8 mm
Nominal outer diameter	9.0 mm
Approximate weight	13.2 kg/100m
Average insulation thickness	0.6 mm
Average sheath thickness	1.2 mm
Neutral conductor section (when smaller)	- mm ²

Electrical characteristics

Rated Voltage U _o /U (U _m)	300 / 500 V
Max. DC resistance of the conductor at 20°C	7.41 Ohm/km

Usage characteristics

Minimum installation temperature	-10 °C
Maximum operating temperature	70 °C
Short-circuit max. conductor temperature	250 °C
Ambient static operating temperature, range	-40 - 70 °C
Length	250 m
Bending factor when laying	5 (xD)
Bending factor when installed	3 (xD)
Packaging	Reel
Smoke density	IEC 61034
Gases corrosivity	IEC 60754-2
U.V resistance	Yes
Installation type	Indoor/Outdoor

SELLING AND DELIVERY INFORMATION

The cable will be delivered in lengths of 50 to 500 m. The drum is marked with manufacturer, type of cable and length.

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Nexans is indicative only and shall not be binding on Nexans or be treated as constituting a representation on the part of Nexans.

Generated 1/6/23 www.nexans.se Page 2 / 2

The logo for Nexans, featuring a stylized red 'N' followed by the word 'Nexans' in a black sans-serif font.