

FQQ 450/750 V (CPR)

FQQ 450/750 V 5G10

Nexans Ref.: 14141498-412-05

Country Ref.: 0406689

The cable may be used for permanent installation on ladders, directly in walls, concrete, in conduits or ducts. For use indoors and outdoors but not in ground or water. The cable have protection against exposure of UV-light.

DESCRIPTION

FQQ is a halogen free, HFFR-insulated and HFFR-sheathed house wiring cable with circular, stranded copper conductors. The cable is designed according to SS 424 02 19-5. The conductors have resistance and number of wires according to IEC 60228 class 2. The cores are identified by colours according to HD 308. Cables with 7 core are numbercoded, (1-6 and yellow/green).The cable has an extruded filler. The sheath is marked. type/manufacturer/year+month/metre marking. FQQ meets the requirements for flammability class Dca-s2,d2,a2 according to CPR and have protection against exposure of UV-light according to HD 626 S1 part 2.5.1. The conductor insulation shall be protected against UV light that can occur for example in light fixtures and light signs. The cable is certified by Intertek SEMKO.

Lifemark(TM) recycling marking

The external surface of the outer sheath is embossed with a text which specifies all components in the polymers and prepares the cable for future recycling.

Certification

Certified by Intertek SEMKO.

Quality and environmental management system

Certified according to ISO 9001, IRIS, ISO/TS 16949 and ISO 14001.



Lifemark™

DECLARATION OF PERFORMANCE

Dca-s2,d2,a2



Conductor flexibility
Stranded class 2



Halogen free
Yes



Rated Voltage Uo/U
(Um)
450 / 750 V



Minimum
installation
temperature
-10 °C



Maximum operating
temperature
70 °C



Smoke density
IEC 61034



Gases corrosivity
IEC 60754-2



Bending factor
installed
6 (xD)

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Nexans is indicative only and shall not be binding on Nexans or be treated as constituting a representation on the part of Nexans.

Generated 1/6/23 www.nexans.fi Page 1 / 2

Nexans

FQQ 450/750 V (CPR)

FQQ 450/750 V 5G10

CHARACTERISTICS

Construction characteristics

Conductor material	Copper
Conductor shape	Circular
Conductor flexibility	Stranded class 2
Insulation	HFFR
Outer sheath	HFFR (polyolefin)
Colour	White
Halogen free	Yes
With Green/Yellow core	-
With smaller neutral conductor	-

Dimensional characteristics

Number of cores	5
Conductor cross-section	10 mm ²
Conductor diameter	- mm
Nominal outer diameter	20.7 mm
Approximate weight	77.0 kg/100m
Average insulation thickness	1.0 mm
Average sheath thickness	1.7 mm
Neutral conductor section (when smaller)	- mm ²

Electrical characteristics

Rated Voltage U ₀ /U (U _m)	450 / 750 V
Max. DC resistance of the conductor at 20°C	1.83 Ohm/km

Usage characteristics

Minimum installation temperature	-10 °C
Recommended minimum installation temperature	0 °C
Maximum operating temperature	70 °C
Short-circuit max. conductor temperature	150 °C
Length	500 m
Packaging	K9
Smoke density	IEC 61034
Gases corrosivity	IEC 60754-2
Bending factor when installed	6 (xD)
Installation type	Indoor/Outdoor
U.V resistance	Yes

SELLING AND DELIVERY INFORMATION

FQQ will be delivered in lengths of 500 m. The drum is marked with manufacturer, type of cable and length.