

PRODUCT-DETAILS

# S20/50M

## GALV.STEEL S SUPERFLEX NC20 50MT



### General Information

Extended Product Type	S20/50M
Product ID	7TCA296010R0067
EAN	5020963000065
Catalog Description	GALV.STEEL S SUPERFLEX NC20 50MT
Long Description	Inherent Low Fire Hazard Steel Conduit, 1/2 Inch, Nominal Conduit Size 20mm, Outside Diameter 20.5mm, Inside Diameter 16.9mm, Static Bend Radius 45mm, Length 50 Meters, Galvanised Steel General Purpose

### Additional Information

Application	Indoors / Outdoors - Light Industrial, Buildings
Product Type	Low Fire Hazard Conduit

### Ordering

EAN	5020963000065
UPC	786210251424
Customs Tariff Number	8307106000

### Dimensions

Product Net Depth / Length	50 m
----------------------------	------

---

## Technical

Number of Batteries	0
Material	Galvanized Steel

---

## Environmental

WEEE Category	Product Not in WEEE Scope
---------------	---------------------------

---

## Container Information

Package Level 1 Units	1 piece
Package Level 1 Height	9.84 in 250 mm
Package Level 1 Depth / Length	16.33 in 415 mm
Package Level 1 Width	16.33 in 415 mm

---

## Certificates and Declarations (Document Number)

Data Sheet, Technical Information	S20/50M
Instructions and Manuals	S20/50M
Declaration of Conformity - CE	9AKK107492A9618
RoHS Information	9AKK107992A8994
RoHS Date	9AKK107992A8994
REACH Declaration	9AKK107992A8994

---

## Classifications

ETIM 8	EC001179 - Protective metallic hose
UNSPSC	39131706

---

## Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

