

PRODUCT-DETAILS

# S25/25M

## GALV.STEEL S SUPERFLEX NC25 25MT



### General Information

Extended Product Type	S25/25M
Product ID	7TCA296010R0092
EAN	5020963000607
Catalog Description	GALV.STEEL S SUPERFLEX NC25 25MT
Long Description	Inherent Low Fire Hazard Steel Conduit, 3/4 Inch, Nominal Conduit Size 25mm, Outside Diameter 25.0mm, Inside Diameter 21.4mm, Static Bend Radius 55mm, Reel Length 25 Meters, Galvanised Steel General Purpose

### Additional Information

Application	Indoors / Outdoors - Light Industrial, Buildings
Product Type	Low Fire Hazard Conduit

### Ordering

EAN	5020963000607
UPC	786210259451
Customs Tariff Number	8307106000

### Dimensions

Product Net Depth / Length	25 m
----------------------------	------

---

**Technical**


---

Number of Batteries	0
Material	Galvanized Steel

---



---

**Environmental**


---

WEEE Category	Product Not in WEEE Scope
---------------	---------------------------

---



---

**Container Information**


---

Package Level 1 Units	1 piece
Package Level 1 Height	7 in 178 mm
Package Level 1 Depth / Length	16 in 406 mm
Package Level 1 Width	16 in 406 mm

---



---

**Certificates and Declarations (Document Number)**


---

Data Sheet, Technical Information	S25/25M
Instructions and Manuals	S25/25M
Declaration of Conformity - CE	9AKK107492A9618
RoHS Information	9AKK107992A8994
RoHS Date	9AKK107992A8994
REACH Declaration	9AKK107992A8994

---



---

**Classifications**


---

ETIM 8	EC001179 - Protective metallic hose
UNSPSC	39131706

---



---

**Categories**


---

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

