

0.038 m

PRODUCT-DETAILS

PMR577

Product Net Width

PMR577 Support



6410011527764 PMR577 Support R577 is used with mounting and junction boxes with knock-out inlets. The port is used for installation of boxes into light, non-bearing walls that are ed on site, with interlayers of 42, 45, 66, 70, 90 and 95 mm. It is possible to or a strain-relief (conduitless flush mounting) with the support. By joining s PMR577 together with an interconnector PMR474 the box groups can be som each other under different covering plates. The center distance of the
PMR577 Support R577 is used with mounting and junction boxes with knock-out inlets. The port is used for installation of boxes into light, non-bearing walls that are ed on site, with interlayers of 42, 45, 66, 70, 90 and 95 mm. It is possible to por a strain-relief (conduitless flush mounting) with the support. By joining s PMR577 together with an interconnector PMR474 the box groups can be com each other under different covering plates. The center distance of the
R577 is used with mounting and junction boxes with knock-out inlets. The port is used for installation of boxes into light, non-bearing walls that are don site, with interlayers of 42, 45, 66, 70, 90 and 95 mm. It is possible to or a strain-relief (conduitless flush mounting) with the support. By joining s PMR577 together with an interconnector PMR474 the box groups can be som each other under different covering plates. The center distance of the
PMR577 Support R577 is used with mounting and junction boxes with knock-out inlets. The sport is used for installation of boxes into light, non-bearing walls that are d on site, with interlayers of 42, 45, 66, 70, 90 and 95 mm. It is possible to or a strain-relief (conduitless flush mounting) with the support. By joining s PMR577 together with an interconnector PMR474 the box groups can be com each other under different covering plates. The center distance of the box groups is 85mm. Made of halogen free material (IEC/61249-2-21).
port is used for installation of boxes into light, non-bearing walls that are ad on site, with interlayers of 42, 45, 66, 70, 90 and 95 mm. It is possible to or a strain-relief (conduitless flush mounting) with the support. By joining s PMR577 together with an interconnector PMR474 the box groups can be som each other under different covering plates. The center distance of the
0
Following EU Directive 2002/95/EC August 18, 2005 and amendment

PMR577 2

Product Net Height	0.018 m
Product Net Depth / Length	0.095 m
Product Net Weight	0.0092 kg

Container Information	
Package Level 1 Units	box 20 piece
Package Level 1 Width	0.016 m
Package Level 1 Height	0.325 m
Package Level 1 Depth / Length	0.4 m
Package Level 1 Gross Weight	0.19 kg
Package Level 1 EAN	6410011527764
Package Level 2 Units	crate 500 piece
Package Level 2 Width	0.4 m
Package Level 2 Height	0.325 m
Package Level 2 Depth / Length	0.4 m
Package Level 2 Gross Weight	5.25 kg
Package Level 3 Units	pallet (lift) 9000 piece
Package Level 3 Width	1.2 m
Package Level 3 Height	1.1 m
Package Level 3 Depth / Length	0.8 m
Package Level 3 Gross Weight	119.16 kg

Ordering	
Minimum Order Quantity	20 piece
Customs Tariff Number	39259080
E-Number (Finland)	1152776
E-Number (Sweden)	1422320
Country of Origin	Finland (FI)

Certificates and Declarations (Document Number)	
Declaration of Conformity - CE	9AKK106713A4627
Instructions and Manuals	9AKK10103A2549
RoHS Information	9AKK106713A4634

Popular Downloads	
Data Sheet, Technical Information	9AKK10103A2549
Instructions and Manuals	9AKK10103A2549

Classifications

ETIM 7 EC002328 - Accessories for junction boxes/junction cases for mounting in the wall

ETIM 8

EC002328 - Accessories/spare parts for junction boxes/cases for mounting in the wall

WEEE Category

Product Not in WEEE Scope

Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Installation\ Materials \rightarrow Flush\ Mounted\ Boxes \rightarrow Accessories\ for\ Plastic\ Flush\ Mounted\ Boxes \rightarrow Box\ Support$

