

## HWD 90 cavity wall boxes



### HWD 90 one-gang box

- For fire-protection walls F30-F120 or EI30 - EI120
- Also for installation shafts / installation ducts I30 - I90
- also for timber frame or timber panel walls EI30-EI60

<b>Article no:</b>	<b>9463-01</b>
EAN:	4013456531659
For panel thickness	7 - 40 mm
Depth	44 mm
Cut hole Ø	74 mm
Screw spacing	60 mm
Cable entries of up to Ø 11.5 mm	2
DIBt approval	Z-19.21-1788
ETA approval	ETA-18/0091
for sound insulation walls up to	77 dB
Halogen-free	Yes
Packaging inner/dispatch	10/100

HWD 90 cavity wall boxes for fire-protection walls F30-F120 or EI30-EI120 ensure certified electrical installation in accordance with fire protection regulations and are now also approved for timber walls in timber frame or timber panel construction EI30 and EI60. No additional measures, such as encasing, are necessary. The intelligent AFS technology reacts immediately to fire and heat and automatically closes the installation opening. This guarantees the fire resistance class of the fire-protection wall and secures emergency routes. Use in all fire-protection walls and the fire-resistance duration of up to 120 minutes ensures maximum flexibility, even when the planning is changed. At the same time, it also maintains the wall's sound insulation requirements.

- For fire-protection walls F30-F120 or EI30 - EI120
- Maintains the wall's sound insulation protection
- Retrofitting also possible
- With fire-protection cover, can be used as a junction box
- Also for directly opposing installation

