#### **OVE Austrian Electrotechnical Association**

Eschenbachgasse 9 | 1010 Wien | Austria

ZVR: 327279890 | www.ove.at

#### **OVE Certification**

Kahlenberger Str. 2A | 1190 Wien | Austria T +43 1 370 58 06 | certification@ove.at

Validity of ÖVE-Certificates can be checked at www.ove.at



Page 1 of 8

# **ÖVE-CERTIFICATE**

including the entitlement to use the Austrian Safety Mark



Certificate No.: 43-168-14 Valid from: 2022 07 25

until: 2023 07 07

The Austrian Electrotechnical Association (OVE) hereby grants the right to the company mentioned below to label the listed products with the Austrian Safety Mark.

Company: PC Electric Ges.m.b.H.

Diesseits 145

4973 St. Martin im Innkreis

Austria

Product: Appliance inlets for industrial purposes

The products submitted by the applicant were type tested in accordance with the requirements of the technical standards and specifications listed in this certificate. OVE certifies the conformity of the listed products and those products manufactured strictly identical to the submitted ones (EN ISO/IEC 17067, Conformity Assessment Scheme Type 5).

The manufacturing process and the products are subject to ongoing surveillance based on harmonized European procedures. This certificate has been issued under the presumption and conditional on the fact that the applicant holds all necessary legal rights with regard to the product, presented for the testing and certification.

Results of testing are shown in file No(s).: 3694-1854/22

Österreichischer Verband für Elektrotechnik

Head of OVE Certification


Digitally signed by T. Neumayer Email=t neumayer@ove.at

Dipl.-Ing. T. Neumayer

OVE

Wien, 2022 07 26









Date: 2022 07 26 Page 2 of 8

#### Manufacturer:

PC Electric Ges.m.b.H. Diesseits 145 4973 St. Martin im Innkreis Austria

#### Factory location(s):

PC Electric Ges.m.b.H. Diesseits 145 4973 St. Martin im Innkreis Austria

#### Tested and certified according to:

ÖVE/ÖNORM EN 60309-1:2013-03-01 ÖVE/ÖNORM EN 60309-2:2013-03-01 IEC 60309-1:2021 IEC 60309-2:2021

This certificate is the basis for the EU Declaration of Conformity and the CE Marking by the manufacturer or his agent and shows the conformity of the certified product(s) with the listed standards as defined by the EU Low-Voltage Directive 2014/35/EU. For the presumption of conformity according to Art. 12 with the safety objectives according to Art. 3 of the Directive, transitional periods given in the Official Journal of the European Union have to be observed.

### **Product: Appliance inlets for industrial purposes**

Type designation: Trademark:

Rating:

543 PCE / ELCEE / SIROX / METECEE

Rated current: 125 A Insulation voltage: 690 V

2P+PE

IP 67 or IP 66/IP 67

with pilot contact, wall mounted appliance-inlet

643 PCE / ELCEE / SIROX / METECEE

Rated current: 125 A Insulation voltage: 690 V

2P+PE

IP 67 or IP 66/IP 67

with pilot contact, appliance-inlet straight





Date: 2022 07 26

Page 3 of 8

743 PCE / ELCEE / SIROX / METECEE

Rated current: 125 A Insulation voltage: 690 V

2P+PE

IP 67 or IP 66/IP 67

with pilot contact, appliance-inlet sloping

544 PCE / ELCEE / SIROX / METECEE

Rated current: 125 A Insulation voltage: 690 V

3P+PE

IP 67 or IP 66/IP 67

with pilot contact, wall mounted appliance-inlet

644 PCE / ELCEE / SIROX / METECEE

Rated current: 125 A Insulation voltage: 690 V

2P+PE

IP 67 or IP 66/IP 67

with pilot contact, appliance-inlet straight

PCE / ELCEE / SIROX / METECEE

Rated current: 125 A Insulation voltage: 690 V

2P+PE

IP 67 or IP 66/IP 67

with pilot contact, appliance-inlet sloping

PCE / ELCEE / SIROX / METECEE 545

Rated current: 125 A Insulation voltage: 690 V

3P+N+PE

IP 67 or IP 66/IP 67

with pilot contact, wall mounted appliance-inlet

645 PCE / ELCEE / SIROX / METECEE

Rated current: 125 A Insulation voltage: 690 V

3P+N+PE

IP 67 or IP 66/IP 67

with pilot contact, appliance-inlet straight

745 PCE / ELCEE / SIROX / METECEE

Rated current: 125 A Insulation voltage: 690 V

3P+N+PE

IP 67 or IP 66/IP 67

with pilot contact, appliance-inlet sloping





Date: 2022 07 26 Page 4 of 8

5432 PCE / ELCEE / SIROX / METECEE

Rated current: 125 A Insulation voltage: 690 V

2P+PE

IP 67 or IP 66/IP 67

without pilot contact, wall mounted appliance-inlet

6432 PCE / ELCEE / SIROX / METECEE

Rated current: 125 A Insulation voltage: 690 V

2P+PE

IP 67 or IP 66/IP 67

without pilot contact, appliance-inlet straight

7432 PCE / ELCEE / SIROX / METECEE

Rated current: 125 A Insulation voltage: 690 V

2P+PE

IP 67 or IP 66/IP 67

without pilot contact, flanged appliance-inlet sloping

5442 PCE / ELCEE / SIROX / METECEE

Rated current: 125 A Insulation voltage: 690 V

3P+PE

IP 67 or IP 66/IP 67

without pilot contact, wall mounted appliance-inlet

6442 PCE / ELCEE / SIROX / METECEE

Rated current: 125 A Insulation voltage: 690 V

3P+PE

IP 67 or IP 66/IP 67

without pilot contact, appliance-inlet straight

7442 PCE / ELCEE / SIROX / METECEE

Rated current: 125 A Insulation voltage: 690 V

3P+PE

IP 67 or IP 66/IP 67

without pilot contact, appliance-inlet sloping

5452 PCE / ELCEE / SIROX / METECEE

Rated current: 125 A Insulation voltage: 690 V

3P+N+PE

IP 67 or IP 66/IP 67

without pilot contact, wall mounted appliance-inlet





Date: 2022 07 26 Page 5 of 8

PCE / ELCEE / SIROX / METECEE

Rated current: 125 A Insulation voltage: 690 V

3P+N+PE

IP 67 or IP 66/IP 67

without pilot contact, appliance-inlet straight


7452 PCE / ELCEE / SIROX / METECEE

Rated current: 125 A Insulation voltage: 690 V

3P+N+PE

IP 67 or IP 66/IP 67

without pilot contact, appliance-inlet sloping







Date: 2022 07 26 Page 6 of 8

# **Typelist**

Туре	Rated current A	Earthing contact pos.	Rated operating voltage V	Frequency Hz
		1	Other ratings	Other ratings
		2	>50	>300 - 500
543		3	>50 - 250	DC
5432		4	100 – 130	50 and 60
643 6432	125	6	200 – 250	50 and 60
743		7	480 – 500	50 and 60
7432		8	>250	DC
1432		9	380 – 415	50 and 60
		10	>50	>100 - 300
		12	Supply from an isolating transformer	50 and 60
		1	Other ratings	Other ratings
	125	2	>50	>300 - 500
F 4 4		3	380	50
544 5442			440	60
644		4	100 – 130	50 and 60
6442		5	600 – 690	50 and 60
744		6	380 – 415	50 and 60
7442		7	480 - 500	50 and 60
7		9	200 – 250	50 and 60
		10	>50	>100 - 300
		11	440 – 460	60
		12	Supply from an isolating transformer	50 and 60
		1	Other ratings	Other ratings
		2	>50	>300 - 500
545		3	220/380	50
5452			250/440	60
645		4	57/100 – 75/130	50 and 60
6452	125	5	347/600 – 400/690	50 and 60
745	120	6	200/346 – 240/415	50 and 60
7452		7	277/480 – 288/500	50 and 60
		9	120/208 – 144/250	50 and 60
		10	>50	>100 - 300
		11	250/440 – 265/460	60
		12	Supply from an isolating transformer	50 and 60





Date: 2022 07 26 Page 7 of 8

## **Typecode**

5	4	_	2	1 -	6	. T	*	*	-	ypecode
1	4	5	1 4	+-	0	<b>)</b>		<u> </u>		
									Contac	ts
								<u> </u>	blank	Nickel plated contacts
									b	uncoated contacts
									Colour	
									blank	Standard type
									*	Reserved for additional colours
									Clock p	position earthing contact
									1	1h
									2	2h
									3	3h
									4	4h
									5	5h
									6	6h
									7	7h
									8	8h
									9	9h
									10	10h
									11	11h
									12	12h
									Custon	ner type
									-	PCE
									Pilot co	
									2	without pilot contact
									blank	with pilot contact
									Poles	
									3	3-poles
									4	4-poles
									5	5-poles
									Rated o	current
									4	125 A
									Ground	
									5	Wall mounted appliance-inlet
									6	Appliance-inlet straight
									7	Appliance-inlet sloping

# **OVE Certification**





Date: 2022 07 26 Page 8 of 8

