



**product description:**

- designed for distribution system with voltage 400 V and with maximum current 16 A
- a large number of knockouts for introducing cables and pipes
- possibility to install the support trunking TS 35
- possibility to set the lid in a horizontal position
- possibility to break the sidewall for easier cable handling
- outer side of the bottom contains holes for marking drill holes
- mounting screws are fitted with a triple thread for quick installation

material: PVC (Pb Free)

color: yellow

self-snuffing: yes, within 30 s

temperature resistance: -5 - +60 °C

flaming loop test: 850 °C

fire class for underlying material: A1-F

weight: 511 g

meets the requirements: EN 60 670-1

storage: ČSN 64 0090

KT 250/L\_NB - cover screws and screws for mounting into double wall inserted into box, each box with a cover sealed in shrink foil and labelled; 12 pcs of boxes stacked in carton

KT 250/L\_ST - screws for mounting into double wall installed in the box, cover screwed to the box and box labelled; 12 pcs of boxes stacked in carton

**accessories:**

- terminal plate S-96; S-96; SP-96
- equipotential terminal plate EPS 2
- screwless terminal plates TYP015, TYP016, TYP017, TYP018
- support trunking TS35

**auxiliary tools:**

- saw-drill VPT 40
- universal carrier VPTU