

Rittal – The System.

Faster – better – everywhere.

Compact enclosure AX Basic enclosure AX, stainless steel – AX 1018.000

Date : Jan 22, 2020

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Compact enclosure AX Basic enclosure AX, stainless steel – AX 1018.000

created: 22.01.2020 build on www.rittal.com/uk-en



Product description

Material:	Enclosure: Stainless steel Door: Stainless steel, all-round foamed-in PU seal Mounting plate: Sheet steel Lock: Die-cast zinc, nickel-plated, double-bit insert stainless steel Stainless steel 1.4301 (AISI 304)
Surface finish:	Enclosure and door: Brushed, grain 400, peak-to-valley height < 0.8 µm Mounting plate: Zinc-plated
Protection category IP to IEC 60 529:	IP 55
Protection category NEMA:	NEMA 12
Type rating to UL 508A:	Type 1, 12
IK Code:	IK08
Supply includes:	Enclosure with door(s), opening angle 130° Mounting plate Lock: 3 mm double-bit
Basic material:	Stainless steel 1.4301 (AISI 304)

Product features

Dimensions:	Width: 1000 mm Height: 1000 mm Depth: 300 mm
--------------------	--

Mounting plate:	Width: 945 mm Height: 975 mm
Number of doors:	2
Number of cam locks:	2
Lock version:	Cam
Number of locks:	2
Lock insert:	3 mm double-bit
Packs of:	1 pc(s).
Weight/pack:	71 kg
EAN:	4028177815049
Customs tariff number:	94032080
ETIM 7.0:	EC000261
ETIM 6.0:	EC000261
eCl@ss 8.0/8.1:	27180101
eCl@ss 6.0/6.1:	27180101
Product description:	AX Compact enclosure, WHD: 1000x1000x300 mm, stainless steel 1.4301, with mounting plate, two-door, with two cam locks