



Main

Product range	Thorsman
Product type	Cable tie
Colour	Natural
Quantity per package	Set of 100

Complementary

Minimum tightening diameter	8,5 mm
Maximum tightening diameter	108 mm
Condition of use	Indoor/outdoor
Resistance to tearing	Resistance to tearing 540 N
Material	PA (polyamide) 6.6 UV-stabilised
Length	380 mm
Width	7,6 mm
Net weight	0,438 kg
Market segment	Small commercial

Environment

Environmental characteristic	Fire resistance needle flame 30 s IEC 60695-11-5
Flame retardance	Self-extinguishing UL 94 V2
Ambient air temperature for operation	-40...85 °C

Pakke osad

Pakendi tüüp 1	PCE
Ühikute arv pakendis 1	1
Package 1 Height	5,7 cm
Pakendi laius 1	16,0 cm
Pakendi pikkus 1	51,0 cm
Pakendi kaal 1	466,0 g
Pakendi tüüp 2	CAR
Ühikute arv pakendis 2	15
Pakendi kõrgus 2	9,5 cm
Pakendi laius 2	39,5 cm
Pakendi pikkus 2	59,5 cm
Pakendi kaal 2	7,8 kg
Pakendi tüüp 3	P12
Ühikute arv pakendis 3	600
Pakendi kõrgus 3	107,0 cm
Pakendi laius 3	80,0 cm
Pakendi pikkus 3	120,0 cm
Pakendi kaal 3	332,0 kg

Offer Sustainability

Jätkusuutliku pakkumise olek	Green Premium toode
REACH-määrus	REACH-deklaratsioon
Ilma SVHC REACH-ta	Jah
ELi RoHS direktiiv	Ennetav vastavus (toode ei jää EL-i RoHS seadustega määratud piiridesse) ELi RoHS deklaratsioon
Mürgiste raskemetallideta	Jah
Elavhõbedavaba	Jah
Hiina EoHS regulatsioon	Hiina RoHS Deklaratsioon
RoHS eranditeave	Jah
Keskkonnavalade avaldus	Toote Keskkonnaprofiil