



Main

Aesthetic name	System M M-Smart M-Elegance M-Plan M-Arc M-Star M-Plan glass
Product or component type	Socket-outlet
Device presentation	Mechanism with central plate
Outlet standard	German
Socket additional information	With hinged lid

Complementary

Outlet poles configuration	2P + E
Wiring device mounting	Flush
Fixing mode	By screws and claws
Rated current	16 A
[Ue] rated operational voltage	250 V
Colour tint	Anthracite RAL 7024)
Connections - terminals	Screwless terminals
Material	Polycarbonate matt

Environment

IP degree of protection	IP44
-------------------------	------

Pakke osad

Pakendi tüüp 1	PCE
Ühikute arv pakendis 1	1
Package 1 Height	5,3 cm
Pakendi laius 1	7,6 cm
Pakendi pikkus 1	7,6 cm
Pakendi kaal 1	102,0 g
Pakendi tüüp 2	CAR
Ühikute arv pakendis 2	50
Pakendi kõrgus 2	18,5 cm
Pakendi laius 2	30,0 cm
Pakendi pikkus 2	40,0 cm
Pakendi kaal 2	5,51 kg

Offer Sustainability

ELi RoHS direktiiv	Uurimisel
WEEE	Tootest tuleb Euroopa Liidu turgudel vabaneda vastavuses erijäätmeseadustele ning see ei tohi sattuda olmeprügi sekka.

Contractual warranty

Garantii	18 months
----------	-----------